Mathematical Modelling of a five stages $n^2 + n$ voltage multiplier's output in the time-domain

Arash Toudeshki^a, Norman Mariun^b, Hashim Hizam^c, Noor Izzri Abdul Wahab^d ^{a,b,c,d}Centre for Advanced Power and Energy Research (CAPER), Faculty of Engineering, University Putra Malaysia, Malaysia ^a<u>arashtoudeshki@gmail.com</u>, ^b<u>norman@eng.upm.edu.my</u>, ^c<u>hashim@eng.upm.edu.my</u>, ^dizzri@eng.upm.edu.my

Abstract: The time-domain behavior of the $n^2 + n$ voltage multiplier was unknown. In this manuscript, we present an optimized approximate mathematical model for the output voltage of a $n^2 + n$ voltage multiplier. The suggested mathematical model includes two components of an exponential recovery equation and a sinusoidal equation which are performing as a function of time and frequency.

Keywords: Mathematical Modelling, voltage multiplier, time-domain, optimization, non-linear least squares.

References:

[1] J.D. Cockcroft, E.T.S. Walton, Experiments with high velocity positive ions. (I) further developments in the method of obtaining high velocity positive ions, Proceedings of the Royal Society of London, Series A, vol. 136, no. 830, pp. 619–630, 1932.

[2] J.F. Dickson, On-chip high-voltage generation in MNOS integrated circuits using an improved voltage multiplier technique, Solid-State Circuits, IEEE Journal of, vol. 11, no. 3, pp. 374–378 1976.

[3] U. Karthaus, M. Fischer, Fully integrated passive UHF RFID transponder IC with 16.7 μ W minimum RF input power, Solid–State Circuits, IEEE Journal of, vol. 38, no. 10, pp. 1602–1608, 2003.

[4] M.S. Makowski, D. Maksimovic, Performance limits of switched-capacitor DC-DC converters, In: Proceedings of PESC'95 – Power Electronics Specialist Conference, IEEE, 1995, vol. 2, pp. 1215–1221, 1995.

[5] J.A. Starzyk, Y.W. Jan, F. Qiu, A DC-DC charge pump design based on voltage doublers, Circuits and Systems I: Fundamental Theory and Applications, IEEE Transactions on, vol. 48, no. 3, pp. 350–359, 2001.

[6] M.S. Makowski, On performance limits of switched–capacitor multi–phase charge pump circuits. Remarks on papers of Starzyk et al., In: 2008 International Conference on Signals and Electronic Systems, no. 1, pp. 309–312, 2008.

[7] A. Toudeshki, Improved Charge Pump for Capacitor Discharge Applications, Ph.D. thesis, Universiti Putra Malaysia, 2013.

[8] A. Toudeshki, N. Mariun, H. Hizam, N.I. Abdul Wahab, Improved charge pump circuit for high-voltage and energy applications using superposition theorem, Majlesi Journal of Energy Management, vol. 2, no. 3, pp. 1–4, 2013.